



> Mechanical Specification:

(1) Dimension

- Chip size: $355 \pm 40 \mu\text{m} \times 280 \pm 40 \mu\text{m}$
- Thickness: 4.3 mil ($110 \pm 10 \mu\text{m}$)
- P bonding pad: 3.1 mil ($80 \pm 10 \mu\text{m}$)
- N bonding pad: 3.1 mil ($80 \pm 10 \mu\text{m}$)

(2) Metallization

- Topside P electrode: Au alloy
- Topside N electrode: Au alloy



Features:

- High luminous intensity
- Long operation life
- 100% probing test
- Passivation layer on top

Applications:

- RGB display

> Electro-optical Characteristics at 25°C: (1)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	Vf1	If = 10μA	1.8	-	-	V
	Vf2	If = 20mA	-	2.7	3.0	V
Reverse Current	I _r	V _r = 5V	-	-	2.0	μA
Dominant Wavelength ⁽²⁾	λ _d	If = 20mA	515	-	535	nm
Spectra Half-width	Δλ	If = 20mA	-	35	-	nm
Luminous intensity ⁽³⁾	I _v	If = 20mA	1500	-	1600	mcd
			1600	-	1700	
			1700	-	1800	
			1800	-	1900	
			1900	-	2000	

Note:

(1) ESD protection during chip handling is recommended.

(2) Basically, the wavelength span is 20nm; however, customers' special requirements are also welcome.

(3) Luminous intensity is measured by EPISTAR's equipment on bare chips.

> Absolute Maximum Ratings:

Parameter	Symbol	Condition	Rating	Unit
Forward DC Current	If	Ta = 25°C	≤ 35	mA
Reverse Voltage	Vr	Ta = 25°C	≤ 5	V
Junction Temperature	Tj	-	≤ 115	°C
Storage Temperature	Tstg	Chip	-40 ~ +85	°C
		Chip-on-tape/storage	5 ~ 35	°C
		Chip-on-tape/transportation	-20 ~ +65	°C
Temperature during Packaging	-	-	280(<10sec)	°C

Note: Maximum ratings are package dependent. The above maximum ratings were determined using a Printed Circuit Board (PCB) without an encapsulant. Stresses in excess of the absolute maximum ratings such as forward current and junction temperature may cause damage to the LED.

> Characteristic Curves:

Fig.1 – Relative luminous Intensity vs. Forward Current




Fig.2 – Forward Current vs. Forward Voltage




Fig.3 – Relative Intensity (@20mA) vs. Ambient Temperature




Fig.4 – Forward Voltage (@20mA) vs. Ambient Temperature




Fig.5 – Dominant Wavelength (@20mA) vs. Ambient Temperature




Fig.6 – Maximum Driving Forward DC Current vs. Ambient Temperature (De-rating based on Tj max. = 115°C)

