


## > Mechanical Specification:

### (1) Dimension

- Chip size: 12 mil x 12 mil (290±25 µm x 290±25 µm)
- Thickness: 3.9 mil (100±15 µm)
- N bonding pad: 3.9 mil (100±10 µm)

### (2) Metallization

- Topside N electrode: Au alloy
- Backside P electrode: Au alloy



### Features:

- High luminous intensity
- Thin film structure
- Vertical electrode
- High driving current

### Applications:

- Outdoor display
- Traffic signal
- Automotive

## > Electro-optical Characteristics at 25°C:

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
<b>Forward Voltage</b>	Vf1	If = 10µA	1.3	-	-	V
	Vf2	If = 20mA	-	2.0	2.5	V
<b>Reverse Current</b>	Ir	Vr = 10V	-	-	5.0	µA
<b>Peak Wavelength</b>	λp	If = 20mA	-	631	-	nm
<b>Dominant Wavelength<sup>(1)</sup></b>	λd	If = 20mA	619	624	629	nm
<b>Spectra Half-width</b>	Δλ	If = 20mA	-	20	-	nm
<b>Luminous Intensity<sup>(2)(3)</sup></b>	Iv	E16	If = 20mA	500	-	-
		E17		550	-	-
		E18		600	-	-
		E19		650	-	-

Note:

(1) Basically, the wavelength span is 10nm; however, customers' special requirements are also welcome.

(2) Customers' special requirements are also welcome.

(3) Luminous intensity is measured by EPISTAR's equipment on bare chips.

## > Absolute Maximum Ratings:

Parameter	Symbol	Condition	Rating	Unit
Forward DC Current	If	T <sub>a</sub> = 25°C	≤ 70	mA
Reverse Voltage	V <sub>r</sub>	T <sub>a</sub> = 25°C	≤ 10	V
Junction Temperature	T <sub>j</sub>	-	≤ 115	°C
Storage Temperature	T <sub>stg</sub>	Chip	-40 ~ +85	°C
		Chip-on-tape/storage	5 ~ 35	°C
		Chip-on-tape/transportation	-20 ~ +65	°C
Temperature during Packaging	-	-	280(<10sec)	°C

Note: Maximum ratings are package dependent. The above maximum ratings were determined using a Printed Circuit Board (PCB) without an encapsulant. Stresses in excess of the absolute maximum ratings such as forward current and junction temperature may cause damage to the LED.

## > Characteristic Curves:

Fig.1 – Relative luminous Intensity vs. Forward Current




Fig.3 – Relative Intensity (@20mA) vs. Ambient Temperature




Fig.5 – Dominant Wavelength (@20mA) vs. Ambient Temperature




Fig.2 – Forward Current vs. Forward Voltage




Fig.4 – Forward Voltage (@20mA) vs. Ambient Temperature




Fig.6 – Maximum Driving Forward DC Current vs. Ambient Temperature (De-rating based on T<sub>j</sub> max. = 115°C)

